



Criteria di scelta delle giranti: in base al diametro massimo

DIAMETRO MAX (mm)	TIPO PALA	MOZZO		MATERIALE PALE	ROTAZIONE DISPONIBILE
		N° PALE	DIAMETRO (mm)		
10000	ES	12	460	AL	A/P
		8	230	PVC	A/P
	SS	10	330	PVC	A/P
		12	460	PVC	A/P
2200	90A	12	460	NV	A
	R10	16	370	NV	R (P)
2040	R10	8	210	NV	R (P)
1610	R14P	12	460	NV	R(P)
1480	R14P	10	330	NV	R(P)
1400	R17 R17PN2	12	460	AL	R (P)
	HWNS 70PN2 SA	12	460	NV	P
1390	R14P	12	240	NV	R(P)
1380	R14P	8	230	NV	R(P)
1330	R14P	9	186	NV	R(P)
1290	R14P	6	140	NV	R(P)
1250	HWN 60A	10	330	AL	A
	HWNS 70P	10	330	NV	P
	HWNS 70PN SA	8	330	NV	P
	SA	10	330	NV	A
	R16	10	330	NV	R(A)
	R16N	8	330	NV	R(A)
1150	HWN 60A	8	230	AL	A
	HWNS 70P	8	230	NV	P
	SA	8	230	NV	A
	SA	6	240	NV	A
1100	R15	10	330	AL	R (A)
	SA	3	186	NV	A
1050	HWN 50P/60A	10	330	AL/NV	A/P
	HWNS 70P/70A	10	330	AL/NV	A/P
	SA	3	140	NV	A
1000	R15	8	230	AL	R (A)
950	HWN 50P/50A	8	230	AL/NV	A/P
	HWNS 70A/70P	8	230	AL/NV	A/P
	R16	8	230	NV	R(A)
900	40 AP	12	240	AL/NV	A/P
	40 AP	9	186	AL/NV	A/P
800	40AP	6	140	AL/NV	A/P