



**Criteria di scelta delle giranti: in base al tipo di pala**

SERIE	TIPO PALA	MOZZO		MATERIALE PALE	ROTAZIONE DISPONIBILE	DIAMETRO MAX (mm)	
		N° MAX PALE	DIAMETRO (mm)				
SMALL	40 AP	6	140	AL/NV	A/P	800	
		9	186	AL/NV	A/P	900	
		12	240	AL/NV	A/P	900	
HWN	50P/60A	8	230	AL/NV	A/P	950	
	60A	8	230	AL/NV	A	1150	
	50P/60A	10	330	AL/NV	A/P	1050	
	60A	10	330	AL/NV	A	1250	
HWNS	70A/70P	8	230	NV	A/P	950	
	70P	8	230	NV	P	1150	
	70A/70P	10	330	NV	A/P	1050	
	70P	10	330	NV	P	1250	
	70PN	8	330	NV	P	1250	
	70AN	8	330	AL	A	1400	
	70PN2	12	460	NV	P	1400	
SA	SA	3	140	NV	A	1050	
		3	186	NV	A	1100	
		6	240	NV	A	1150	
		8	230	NV	A	1150	
		8	330	NV	A	1250	
		10	330	NV	A	1250	
90A	90A	12	460	NV	A	1400	
		12	460	NV	A	2200	
		8	230	PVC	A/P		
		10	330	PVC	A/P	10000	
		12	460	PVC	A/P		
ES	ES	12	460	AL	A/P	10000	
		8	230	NV	R(A)	950	
REVERSIBILI	R16	10	330	NV	R(A)	1250	
	R16N	8	330	NV	R(A)	1250	
	R15	8	230	AL	R(A)	1000	
		10	330	AL	R(A)	1100	
	R17 R17PN2	12	460	AL	R(P)	1400	
	R10	8	210	NV	R(P)	2040	
		16	370	NV	R(P)	2200	
	R14P	R14P	6	140	NV	R(P)	1290
			9	186	NV	R(P)	1330
			12	240	NV	R(P)	1390
			8	230	NV	R(P)	1380
10			330	NV	R(P)	1480	
		12	460	NV	R(P)	1610	