



## Way to choose impellers: max diameter

MAX DIAMETER (mm)	BLADE TYPE	BLADES N°	HUB DIAMETER (mm)	BLADE MATERIAL	AVAILABLE ROTATORY
<b>10000</b>	ES	12	460	AL	A/P
		8	230	PVC	A/P
	SS	10	330	PVC	A/P
		12	460	PVC	A/P
<b>2200</b>	90A	12	460	NV	A
<b>2040</b>	R10	16	370	NV	R (P)
	R10	8	210	NV	R (P)
<b>1610</b>	R14P	12	460	NV	R(P)
<b>1480</b>	R14P	10	330	NV	R(P)
<b>1400</b>	R17 R17PN2	12	460	AL	R (P)
	HWNS 70PN2 SA	12	460	NV	P
<b>1390</b>	R14P	12	240	NV	R(P)
<b>1380</b>	R14P	8	230	NV	R(P)
<b>1330</b>	R14P	9	186	NV	R(P)
<b>1290</b>	R14P	6	140	NV	R(P)
<b>1250</b>	HWN 60A	10	330	AL	A
	HWNS 70P	10	330	NV	P
	HWNS 70PN SA	8	330	NV	P
	SA	10	330	NV	A
	R16	10	330	NV	R(A)
	R16N	8	330	NV	R(A)
<b>1150</b>	HWN 60A	8	230	AL	A
	HWNS 70P	8	230	NV	P
	SA	8	230	NV	A
	SA	6	240	NV	A
<b>1100</b>	R15	10	330	AL	R (A)
	SA	3	186	NV	A
<b>1050</b>	HWN 50P/60A	10	330	AL/NV	A/P
	HWNS 70P/70A	10	330	AL/NV	A/P
	SA	3	140	NV	A
<b>1000</b>	R15	8	230	AL	R (A)
<b>950</b>	HWN 50P/50A	8	230	AL/NV	A/P
	HWNS 70A/70P	8	230	AL/NV	A/P
	R16	8	230	NV	R(A)
<b>900</b>	40 AP	12	240	AL/NV	A/P
	40 AP	9	186	AL/NV	A/P
<b>800</b>	40AP	6	140	AL/NV	A/P